



Propuneri interventii
punere in valoare descoperiri arheologice Z5



SECTIUNE TRANSVERSALA



- pardoseala piatra Vrata - 20mm grosime
- sapa slab armata - 50mm
- polistiren extrudat 100mm
- planseu BA - 150mm
- strat rupere capilaritate - 30cm
- pereta BA - 200mm
- impermeabilizare beton cu cimenturi osmotice tip Vandex sau similar - 2 straturi
- zidarie aparenta caramida plina presata - mortar de var hidraulic

NR. CRT.	DESCRIERE	DIMENSIUNI		CANT.	MP	TOTAL MP	destinatie
		L (mm)	H (mm)				
P3	pardoseala sticla laminata - tratament antiderapant sticla float clara securizata, triplu laminata 30 mm (10.2.10.2.10 mm) lipita pe un cadru din grinzi metalice protejate cu vopsea termosfumanta cu garnitura de etansare la imbinarea placilor de sticla	6712	2180	1 buc.		14.63	parter P12
P3.1	perforatii Ø15mm - interval 100mm - 56buc /panou	590	2180	2 buc.	1.29	2.58	
P3.2		550	2180	9 buc.	1.20	10.80	
P3.3	perforatii Ø15mm - interval 100mm - 41buc / panou	550	1575	1 buc.	0.87	0.87	
P3.4	panou mobil - pivotant	550	550	1 buc.	0.3	0.3	

intocmit: arh. Ruxandra Capatana
sef proiect: arh. Virgiliu Polizu