

tola metalica grosime 5mm  
- vopsita in camp electrostatic RAL 7024

NR. CRT.	DESCRIERE	DIMENSIUNI		CANT.	MP	TOTAL MP	destinatie
		L (mm)	H (mm)				
B1	balustrada sticla cu grosime de 16 mm clara, finisata, gaurita, securizata, dublu-laminata 8.2.8 mm montata in profil metalic "U" la partea inferioara	6010	1050	1 buc.		6.3	subsol S01
B1.1		900	1050	6 buc.	0.95	5.7	
B1.2	panou mobil - deschidere batanta	600	995	1 buc.	0.6	0.6	
P1	pardoseala sticla laminata - tratament antiderapant sticla float clara securizata, triplu laminata 30 mm (10.2.10.2.10 mm) montata pe picioruse metalica reglabile si papuc de cauciuc la partea inferioara	3000	500	1 buc.		1.5	subsol S08
P1.1		1495	500	2 buc.	0.75	1.5	

SECTIUNE TRANSVERSALA ZONA Z1


mana curenta lemn stejar stratificat, finisaj  
- lac pe baza de apa - culoare natur  
prindere cu distanteri metalici pe sticla  
150x40mm

balustrada  
sticla cu grosime de 16 mm clara, finisata, gaurita, securizata, dublu-laminata 8.2.8 mm  
montata in profil metalic "U" la partea inferioara

pardoseala caramida dublu presata 24x11,5x4,5cm  
mortar de poza  
sapa slab armata 5cm  
polistiren extrudat 10cm  
placa beton armat 10cm  
folie polietilena

tola metalica grosime 5mm  
- vopsita in camp electrostatic RAL 7024  
pietris margaritar granulat 10-30mm

vestigii canalizare romana  
conservarea se va face conform indicatiilor  
- expert conservator vestigii epoca romana



cota interioara canalizare romana  
pardoseala de sticla nu va intra in contact direct cu caramida canalizarii  
se vor utiliza distanteri metalici si papuci de cauciuc la contactul cu caramida

VEDERE / SECTIUNE PARDOSEALA ZONA Z2